PATENT ABSTRACTS OF JAPAN

(11) Publication number:

08300418 A

(43) Date of publication of application: 19.11.1996

(51) Int. CI

B29C 45/28

B29C 45/04, B29C 45/74

(21) Application number:

07105595

(71) Applicant: IKEGAMI KANAGATA KOGYO KK

(22) Date of filing:

28.04.1995

(72) Inventor: **SUZUKI JIRO**

COPYRIGHT: (C)1996,JPO

(54) INJECTION MOLDING DIE

(57) Abstract:

PURPOSE: To provide an injection molding die in which resin flows uniformly into a cavity, and a pressure loss is reduced and which can give a high quality molded product.

CONSTITUTION: A movable die 3 which can advance/back to/from a fixed die 2 is provided, and a cavity 35 is formed between the dies 2, 3. A resin injection port, a resin passage 25a which communicates with the port, and a ring-shaped gate 30 which communicates with the passage 25a and leads molten resin to the cavity 35 are installed. In addition, a sleeve guide needle 31 is installed which is bonded/supported to/by a cavity core 36 which penetrates the passage 25a and the gate 30 and forms the cavity by its end part, and a sleeve valve 33 which opens/closes the gate 30 freely advansingly/backingly in the axial direction is engaged with the needle 31.



